



Polycom® SoundPoint® IP 550

Cutting-edge SIP feature set meets Polycom HD Voice™

HDvoice



Benefits

Revolutionary Voice Quality –

Polycom HD Voice technology enables life-like richness, clarity, and interactivity of voice communications⁵

Advanced Features & Applications¹ –

- Four lines
- Backlit 320 x 160-pixel graphical grayscale LCD
- Shared call/bridged line appearance
- Busy lamp field (BLF)
- Presence, buddy lists
- XHTML micro-browser for Web applications

Efficient Installation and Provisioning –

- Integrated IEEE 802.3af Power over Ethernet (PoE) support
- Remote, zero-touch provisioning with support of a variety of servers

Broad Interoperability –

Certified to support a comprehensive set of features with a variety of leading SIP-based IP PBX and Softswitch platforms² and to interoperate with Microsoft Live Communications Server for telephony and presence⁴

Revolutionary sound quality and advanced features in a four-line SIP phone

Introducing the SoundPoint IP 550 desktop phone, a four-line SIP phone that delivers calls of unprecedented richness and clarity and supports a comprehensive range of cutting-edge features.

Unparalleled Sound Quality

The SoundPoint IP 550 desktop phone features Polycom's revolutionary HD Voice™ technology, which brings life-like richness and clarity to every call.⁵ Polycom HD Voice technology incorporates wideband audio for over twice the voice clarity; Polycom's patented Acoustic Clarity Technology for crystal-clear, noise- and echo-free sound, plus best-in-class system design for high-fidelity, faithful voice reproduction.

Comprehensive, Cutting-Edge Feature Set¹

The SoundPoint IP 550 desktop phone delivers advanced features and capabilities, such as shared call/ bridged line appearance, busy lamp field (BLF), presence, text messaging, and buddy lists. The SoundPoint IP 550 phone also boasts an integrated XHTML micro-browser that allows users to take advantage of productivity-enhancing Web-based applications. Add the support of four lines, a backlit, high-resolution, easy-to-read graphical display and flexible customisations options, and it becomes clear why the SoundPoint IP 550 is certain to meet the voice communication needs of the most demanding managers and professionals.

Efficient Installation and Provisioning

The SoundPoint IP 550 desktop phone is engineered to make installation, configuration, and upgrades as simple and efficient as possible. The phone's built-in IEEE 802.3af PoE circuitry and a dual-port Ethernet switch enable flexible deployment options and savings on cabling expenses. The SoundPoint IP 550 phone supports remote, zero-touch provisioning and upgrades from a variety of servers, including FTP, TFTP, HTTP³, or HTTPS³. To ensure reliable, uninterrupted performance, the phone supports boot⁴ and call server redundancy.

Broad Interoperability

The SoundPoint IP 550 desktop phone has been tested and certified to deliver comprehensive interoperability and extensive feature support with leading SIP-based call control platforms by BroadSoft, Sylanro, Interactive Intelligence/Vonexus, Digium, and other Polycom Technology and Interoperability Partners². The phone also interoperates with Microsoft® Live Communications Server (LCS) 2005 for telephony and presence. Therefore, whether the SoundPoint IP 550 phone is deployed in conjunction with an IP PBX or a hosted VoIP service, you can rely on it to deliver on its promise of outstanding sound quality and industry-leading SIP feature set.

 POLYCOM®

TOGETHER, GREAT THINGS HAPPEN.

VIDEO

VOICE

DATA

WEB

Make Great Things Happen with Polycom SoundPoint IP 550 Desktop Phone

In today's Internet driven world, the ability to conduct real time communication and collaboration has become critical to an organisation's survival. As the market leader in voice, video, data and Web solutions, our award-winning conference technology makes it easy for people to interact and maximise productivity – over any network, in just about any environment, anywhere around the globe. That's why more organisations worldwide use and prefer Polycom conferencing solutions. Because when people work together, great things happen. See how you, too, can achieve great things with the Polycom SoundPoint IP 550 desktop phone.

SPECIFICATIONS

Lines (Directory Numbers)

- Up to 4 lines with up to 2 concurrent calls per line

Display

- 320 x 160-pixel backlit grayscale graphical LCD
- White LED backlight with custom intensity control

Feature Keys

- 4 context-sensitive "soft" keys
- 26 dedicated "hard" keys
 - 4 line keys with bi-colour (red/green) LED
 - 8 feature keys
 - 6 display/menu navigation keys
 - 2 volume control keys
 - Illuminated mute key
 - Illuminated headset key
 - Illuminated hands-free speakerphone key
 - Dedicated hold key

Headset Compatibility

- Dedicated RJ-9 headset port
 - Amplified headsets are recommended

Hearing Aid Compatibility

- Compliant with ADA Section 508 Recommendations: Subpart B 1194.23 (all)
- Hearing Aid Compatible (HAC) handset for magnetic coupling to approved HAC hearing aids
- Compatible with commercially-available TTY adaptor equipment

Audio Features

- Polycom HD Voice technology delivers life-like voice quality for each audio path - the handset, the hands-free speakerphone, and the optional headset^{1,5}
- Full-duplex hands-free speakerphone
 - Type 1 compliant with IEEE 1329 full duplex standards
- Frequency response - 100Hz - 7kHz for handset, optional headset and hands-free speakerphone modes
- Codecs: G.722 (wideband), G.711 μ /A, and G.729A (Annex B)
- Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise fill
- DTMF tone generation / DTMF event RTP payload
- Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment
- Acoustic echo cancellation
- Background noise suppression

Call Handling Features¹

- Shared call / bridged line appearance
- Flexible line appearance (one or more line keys can be assigned for each line extension)
- Busy Lamp Field (BLF)
- Distinctive incoming call treatment / call waiting
- Call timer
- Call transfer, hold, divert (forward), pickup
- Called, calling, connected party information
- Local three-way conferencing
- One-touch speed dial, redial
- Call waiting
- Remote missed call notification
- Intercom
- Automatic off-hook call placement
- Do not disturb function

Other Features

- Interoperability with Microsoft LCS 2005 for telephony and presence⁴
- Local feature-rich GUI
- Time and date display
- User-configurable contact directory and call history (missed, placed, and received)
- Customisable call progress tones
- Wave file support for call progress tones
- Unicode UTF-8 character support. Multilingual user interface encompassing Chinese, Danish, Dutch, English (Canada / US / UK), French, German, Italian, Japanese, Korean, Norwegian, Portuguese, Russian, Spanish, Swedish

Protocol Support

- IETF SIP (RFC 3261 and companion RFCs)

Network and Provisioning

- Two-port 10/100 Mbps Ethernet switch
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronisation using SNTP
- FTP / TFTP / HTTP² / HTTPS² server-based central provisioning for mass deployments
- Provisioning¹ and call server redundancy supported
- Web portal for individual unit configuration
- QoS Support – IEEE 802.1p/Q tagging (VLAN), Layer 3 TOS, and DSCP
- Network Address Translation (NAT) – support for static configuration and "Keep-Alive" SIP signalling
- RTCP support (RFC 1889)
- Event logging
- Syslog
- Local digit map
- Hardware diagnostics
- Status and statistics reporting

Security¹

- Transport Layer Security (TLS)⁴
- Encrypted configuration files⁴
- Digest authentication
- Password login
- Support for URL syntax with password for boot server address
- HTTPS secure provisioning³
- Support for signed software executables³

Power

- Built-in, auto-sensing IEEE 802.3af Power over Ethernet
- External Universal input AC adaptor (included; 24V DC @ 500mA min.)

Approvals

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- AS/NZS CISPR 22 Class B
- VCCI Class B
- EN55024
- EN61000-3-2; EN61000-3-3
- ROHS compliant
- Anatel
- GOST
- C-tick
- CCC

Safety

- CE Mark
- EN 60950-1
- IEC 60950-1
- AS/NZS 60950-1
- UL/C-UL

Operating Conditions

- Temperature: +10 to 40°C (+50 to 104°F)
- Relative Humidity: 20% to 85%, non-condensing

Storage Temperature

- -40 to +70°C (-40 to +160°F)

SoundPoint IP 550 Comes With:

- SoundPoint IP 550 console
- Handset with handset cord
- Base stand
- Network (LAN) cable
- Universal power adaptor (including country-specific cord kit)
- Quick Start Guide
- Product registration card

Size

- 26.5 cm x 15 cm x 19 cm x 6.5 cm (10.5 in x 6 in x 7.5 in x 2.5 in) (W x H x D x T)

Weight

- Phone weight: 1.26 kg (2.75 lb)

Part Numbers / UPC Codes

- 2200-12550-001 / 610807526773 for NA, CALA, Taiwan
- 2200-12550-002 / 610807526766 for Japan
- 2200-12550-012 / 610807526759 for Australia, New Zealand
- 2200-12550-015 / 610807526742 for UK, Ireland, HK, Singapore, Malaysia
- 2200-12550-016 / 610807526902 for Korea
- 2200-12550-022 / 610807526919 for China
- 2200-12550-122 / 610807526735 for Europe, India, Rest of the World

Unit Box Dimensions / Weight

- 31.7 cm x 33.6 cm x 8.8 cm (12.5 in x 13.25 in x 3.5 in)
- 2 kg (2045 g)

Master Carton Quantity

- Five

Country of Origin

- Thailand

Warranty

- 1 year

¹ Some of these features need to be supported by an appropriate call / applications server.

² Please visit <http://www.polycom.com/techpartners.htm> for a list of supported platforms.

³ Requires BootROM version 3.2.x or higher.

⁴ Requires SIP version 2.0.x or higher.

⁵ In some calling scenarios, such as IP to PSTN, Polycom HD Voice will not be available and the call will progress in narrowband instead.

©2007 Polycom, Inc. All rights reserved.

Polycom, the Polycom logo and SoundPoint are registered trademarks and Polycom HD Voice is a trademark of Polycom, Inc. in the U.S. and various countries. All other trademarks are the property of their respective owners. Specifications subject to change without notice.



Polycom EMEA Headquarters: 270 Bath Road, Slough, Berkshire SL1 4DX, United Kingdom, (T) +44 (0)1753 723000, (F) +44 (0)1753 723010
Polycom (France) Sarl: Tour Areva, 31 éme étage, 1 place de la Coupole, 92084 la Defense, Paris, France, (T) +33 141 321 999, (F) +33 141 321 998
Polycom (Germany) GmbH: Am Soldnermoos 17, 85399 Hallbergmoos, Germany, (T) +49 (0)811-9994 - 100, (F) +49 (0)811-9994 - 200
Polycom (Italy) S.r.l. Via Rivoltana 2/d, 20090 Segrate, MI, Italy, (T) Numero verde 800 13 55 98, (F) +39 02 75 39 92 49
Polycom (Spain) S.A. Lopez de Hoyos 35 - 1º, 28002 Madrid, Spain, (T) +34 91 7459973, (F) +34 91 7459999
Polycom Headquarters: 4750 Willow Road, Pleasanton, CA 94588 (T) 1.800.POLYCOM (765.9266) for North America only.

Part No. 3726-17680-002 Rev. 03/07